

**CLAIMS**

1. A method, comprising:  
moving at least one of a first image picked up with a pickup  
5 apparatus in a predetermined first state and a second image picked up  
with the pickup apparatus in a second state different from the first state;  
and  
adjusting a position of fusion of an object designated in the first  
and second images to generate a stereoscopic image.  
10
2. The stereoscopic-image generating method as specified in claim 1,  
characterized in that the second state is the state that the pickup apparatus  
which carries out pickup in the first state is moved parallel with respect to a  
pickup face.  
15
3. The stereoscopic-image generating method as specified in  
claim 1, characterized in that the second state is the state that the pickup  
apparatus which carries out pickup in the first state is rotated to a position  
where with any point on an extension of a connecting line connecting the  
20 pickup apparatus and a pickup target object on the side of the pickup  
apparatus as center, an optical axis of the pickup apparatus forms a  
predetermined angle with respect to the connecting line.
4. The stereoscopic-image generating method as specified in claim 1,  
25 characterized in that condenser-type optical means are disposed between a  
pickup element of the pickup apparatus and a pickup target object, the  
condenser-type optical means being movable to any position holding an  
optical axis parallel to the optical axis of the pickup apparatus,  
wherein the first state is the state before movement of the  
30 condenser-type optical means, and

wherein the second state is the state after movement of the condenser-type optical means.

5        5.        The stereoscopic-image generating method as specified in claim 1, characterized in that angle controlling means are disposed between a pickup element of the pickup apparatus and a pickup target object, the angle controlling means controlling an outgoing angle of light emitted to a pickup face of the pickup apparatus,

             wherein the first state is the state that the outgoing angle of the  
10    angle controlling means are controlled at a first angle, and

             wherein the second state is the state that the outgoing angle of the angle controlling means are controlled at a second angle different from the first angle.

15        6.        The stereoscopic-image generating method as specified in claim 5, characterized in that the angle controlling means comprise a variable apex-angle prism.

20        7.        The stereoscopic-image generating method as specified in claim 5, characterized in that light transmitting means with a light entering face and a light exiting face formed parallel to each other are arranged on a path connecting a pickup element of the pickup apparatus and a pickup target object to be insertable at a predetermined angle,

             wherein the first state is the state that the light transmitting means  
25    fail to be inserted on the path, and

             wherein the second state is the state that the light transmitting means are inserted on the path.

30        8.        The stereoscopic-image generating method as specified in claim 7, characterized in that the light transmitting means comprise a transparent

parallel plate.

9. A stereoscopic-image generating apparatus, characterized in that it comprises:

5 Image moving means for moving at least one of a first image picked up with a pickup apparatus in a predetermined first state and a second image picked up with the pickup apparatus in a second state different from the first state, the image moving means adjusting a position of fusion of an object designated in the first and second images to generate  
10 a stereoscopic image.

10. The stereoscopic-image generating apparatus as specified in claim 9, characterized in that it comprises frame-image generating means for generating a frame image based on the moved at least one of the first  
15 and second images.

11. The stereoscopic-image generating apparatus as specified in claim 9, characterized in that it comprises shift-amount setting means for setting a shift amount of the first and second images.  
20

12. The stereoscopic-image generating apparatus as specified in claim 9, characterized in that it comprises mode selecting means for selecting a shift mode of the first and second images.

25 13. The stereoscopic-image generating apparatus as specified in claim 9, characterized in that the second state is the state that the pickup apparatus which carries out pickup in the first state is moved parallel with respect to a pickup face.

30 14. The stereoscopic-image generating apparatus as specified in

claim 9, characterized in that the second state is the state that the pickup apparatus which carries out pickup in the first state is rotated to a position where with any point on an extension of a connecting line connecting the pickup apparatus and a pickup target object on the side of the pickup apparatus as center, an optical axis of the pickup apparatus forms a predetermined angle with respect to the connecting line.

15. The stereoscopic-image generating apparatus as specified in claim 9, characterized in that condenser-type optical means are disposed between a pickup element of the pickup apparatus and a pickup target object, the condenser-type optical means being movable to any position holding an optical axis parallel to the optical axis of the pickup apparatus, wherein the first state is the state before movement of the condenser-type optical means, and wherein the second state is the state after movement of the condenser-type optical means.

16. The stereoscopic-image generating apparatus as specified in claim 9, characterized in that angle controlling means are disposed between a pickup element of the pickup apparatus and a pickup target object, the angle controlling means controlling an outgoing angle of light emitted to a pickup face of the pickup apparatus, wherein the first state is the state that the outgoing angle of the angle controlling means are controlled at a first angle, and wherein the second state is the state that the outgoing angle of the angle controlling means are controlled at a second angle different from the first angle.

17. The stereoscopic-image generating apparatus as specified in claim 16, characterized in that the angle controlling means comprise a

variable apex-angle prism.

18. The stereoscopic-image generating apparatus as specified in claim 9, characterized in that light transmitting means with a light entering  
5 face and a light exiting face formed parallel to each other are arranged on a path connecting a pickup element of the pickup apparatus and a pickup target object to be insertable at a predetermined angle,

wherein the first state is the state that the light transmitting means fail to be inserted on the path, and

10 wherein the second state is the state that the light transmitting means are inserted on the path.

19. The stereoscopic-image generating apparatus as specified in claim 18, characterized in that the light transmitting means comprise a  
15 transparent parallel plate.